



WATER LEVEL SEQUENCE



BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION	BY	REPRESENTATIVE
A.(1) STEAM OUTLET	6" 300# FLANGE	HORSEPOWER	300*					?
B.(4) LWCO	1" NPT	DESIGN PRESSURE	150 PSI STEAM					
C.(2) SAFETY VALVE	2" NPT	GROSS OUTPUT	10043 MBH*					
D.() SAFETY VALVE		STEAM (FROM & AT 212°F)	10350 Lb/H*					
E.(2) BOILER BLOWDOWN	1 1/2" NPT	HEAT RELEASE: (FURNACE ONLY)	181043 Btu/CuFt*					
F.(1) SURFACE BLOWDOWN	1" NPT	RATED INPUT	125533MBH*					
G.(1) MAINWAY	12" x 16"	HEATING SURFACE (ASME)	15193Sbf					
H.(4) HANDHOLE	3" x 4"	FURNACE HEATING SURFACE	112.30 SqFt					
J.(1) CLEANOUT	17" ID	FURNACE VOLUME:						
K.(2) FEEDWATER	2" NPT	FURNACE ONLY	69.34 CuFt					
L.(1) AUXILIARY/VENT	2" NPT	STEAMING VOLUME	34.41 CuFt					
M.(1) LOW FIRE HOLD	1" NPT	STEAM RELEASE AREA	54.20 SqFt					
N.(1) STACK TEMP	1/2" NPT	WATER CAPACITY:						
P.(1) SIGHTPORT	1" PIPE	(FULL)	1,790 Gal					
Q.()		(NWL)	1,533 Gal					
R.()		SHIPPING WEIGHT:	22,300 Lbs					
S.()								

NOTES		SUPERIOR BOILER		CHECKED BY	DATE
1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.		APACHE		DRAWN BY	DATE
2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.				X	
3. REAR DOOR SWING:		BOILER MODEL			
(1) MIN SIDE, MAX REAR		8-5-1500-S150-			
(2) MAX SIDE, MIN REAR		DRAWING No			
4. BOILER DESIGN CODE ASME SECTION I		1/50			
5. BOILER INSULATED WITH 2" - 8# DENSITY MINERAL FIBER INSULATION WITH 22 GAUGE STEEL JACKET.					
6. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.					
*7. HORSEPOWER & RELATED INFO BASED ON 5 SqFt FIRING.					

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.	
---	--