



BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION	BY	REPRESENTATIVE:
A.(1) STEAM OUTLET	4" 300# FLANGE	HORSEPOWER	150					?
B.(4) LWCO	1" NPT	DESIGN PRESSURE	150 PSI STEAM					
C.(2) SAFETY VALVE	2" NPT	GROSS OUTPUT	5021 MBH					
D.() SAFETY VALVE		STEAM (FROM & AT 212°F)	5175 LBS/HR					
E.(1) BOILER BLOWDOWN	1 1/4" NPT	HEAT RELEASE: (FURNACE ONLY)	136195 BTU/CuFt					PROJECT:
F.(1) SURFACE BLOWDOWN	1" NPT	RATED INPUT	6277 MBH					?
G.(1) MANWAY	12" x 16"	HEATING SURFACE (ASME)	760 SqFt					
H.(5) HANDHOLE	3" x 4"	FURNACE HEATING SURFACE	84.71 SqFt					
J.(1) CLEANOUT	17" ID	FURNACE VOLUME	46.09 CuFt					
K.(2) FEEDWATER	1 1/4" NPT	TURNAROUND VOLUME	24.09 CuFt					
L.(1) AUXILIARY/VENT	2" NPT	STEAMING VOLUME	26.03 CuFt					
M.(1) LOW FIRE HOLD	1" NPT	STEAM RELEASE AREA	49.45 SqFt					
N.(1) STACK TEMP	1/2" NPT	WATER CAPACITY:						
P.(1) SIGHTPORT	1" NPT	(FULL)	1,535 GAL @ 12,766 LBS					
Q.()		(NWL)	1,340 GAL @ 11,147 LBS					
R.()		SHIPPING WEIGHT:	14,900 LBS					
S.()								

NOTES			
1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET. 2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET. 3. BOILER DESIGN CODE ASME SECTION I. 4. BOILER INSULATED WITH 2" OF INSULATION WITH 22 GAUGE STEEL JACKET. 5. ALL DIMENSION ARE ±1/2" UNLESS OTHERWISE NOTED.			

	CHECKED BY	DATE	THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.
	DRAWN BY	DATE	
BOILER MODEL			
DRAWING No			
SCALE	7-5-750-S150		
1/48	?		