



BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION	BY	REPRESENTATIVE:
A.(1) STEAM OUTLET	6"-300# FLANGE	HORSEPOWER	350					X
B.(4) LWCO	1" NPT	DESIGN PRESSURE	150 PSI STEAM					
C.(2) SAFETY VALVE	2" NPT	GROSS OUTPUT	11,716 MBH					
D.() SAFETY VALVE		STEAM (FROM & AT 212°F)	12,075 LB/HR					
E.(2) BOILER BLOWDOWN	1 1/2" NPT	HEAT RELEASE: (FURNACE ONLY)	134,468 BTU/CuFt					
F.(1) SURFACE BLOWDOWN	1" NPT	RATED INPUT	14,645 MBH					
G.(1) MANWAY	12" x 16"	HEATING SURFACE (ASME)	1,783 SqFt					
H.(4) HANDHOLE	3" x 4"	FURNACE HEATING SURFACE	159.03 SqFt					
J.(1) CLEANOUT	17" ID	FURNACE VOLUME:						
K.(2) FEEDWATER	2" NPT	FURNACE ONLY	108.91 CuFt					
L.(1) AUXILIARY	2" NPT	STEAMING VOLUME	56.15 CuFt					
M.(1) LOW FIRE HOLD	1/2" NPT	STEAM RELEASE AREA	76.95 SqFt					
N.(1) STACK TEMP	1/2" NPT	WATER CAPACITY:						
P.()		(FULL)	2,802 GAL @ 23,303 Lbs					
Q.()		(NWL)	2,382 GAL @ 19,810 Lbs					
R.()		SHIPPING WEIGHT:	29,000 Lbs					
S.()								

NOTES			
1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET. 2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET. 3. REAR DOOR SWING: (1) MIN SIDE, MAX REAR (2) MAX SIDE, MIN REAR 4. BOILER DESIGN CODE ASME SECTION II 5. BOILER INSULATED WITH 2" - 8# DENSITY MINERAL FIBER INSULATION WITH 22 GAUGE STEEL JACKET. 6. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED. *7. HORSEPOWER & RELATED INFO BASED ON 5 SqFt FIRING.			

	CHECKED BY	DATE	THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.
	DRAWN BY	DATE	
BOILER MODEL			
MOHAWK	4-5-1758-S150-		
SCALE	DRAWING No		
1/64	?		