



BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION	BY	REPRESENTATIVE:
A.(1) STEAM OUTLET	12" 150# FLANGE	HORSEPOWER	500*					?
B.(4) LWCO	1" NPT	DESIGN PRESSURE	15 PSIG STEAM					
C.(3) SAFETY VALVE	3" NPT	GROSS OUTPUT	16738 MBH*					
D.( ) SAFETY VALVE		STEAM (FROM & AT 212°F)	17250 LB/HR*					
E.(2) BOILER BLOWDOWN	2" NPT	HEAT RELEASE: (FURNACE ONLY)	141,242*					PROJECT:
F.(1) SURFACE BLOWDOWN	1" NPT	RATED INPUT	20922 MBH*					?
G.(1) MANWAY	12" x 16"	HEATING SURFACE (ASME)	2515 SqFt					
H.(4) HANDHOLE	3" x 4"	FURNACE HEATING SURFACE	172.86 SqFt					
J.(1) CLEANOUT PORT	17" ID	FURNACE VOLUME:						
K.(2) FEEDWATER	2" NPT	FURNACE ONLY	148.13 CuFt					
L.(1) AUXILIARY/VENT	2" NPT	STEAMING VOLUME	76.33 CuFt					
M.(1) LOW FIRE HOLD	1/2" NPT	STEAM RELEASE AREA	91.91 SqFt					
N.(1) STACK TEMP	1/2" NPT	WATER CAPACITY:						
P.(1) SIGHT PORT	1 1/4" PIPE	(FULL)	3,716 Gal @ 30,905 Lbs					
Q.( )		(NWL)	3,145 Gal @ 26,155 Lbs					
R.( )		SHIPPING WEIGHT:	39,500 Lbs					
S.( )								

  

NOTES			
1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.			
2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.			
3. REAR DOOR SWING: (1) MIN SIDE, MAX REAR (2) MAX SIDE, MIN REAR			
4. BOILER DESIGN CODE ASME SECTION IV			
5. BOILER INSULATED WITH 2" OF INSULATION WITH 22 GAUGE STEEL JACKET.			
6. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.			
*7. HORSEPOWER AND RELATED INFO BASED ON 5 SqFt FIRING			

  

	CHECKED BY	?	DATE	THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.
	DRAWN BY	?	DATE	
BOILER MODEL		4-5-2506-S15-GP		
SCALE	DRAWING No		?	
1/70				