



BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION	BY	REPRESENTATIVE:
A.(1) STEAM OUTLET	6"-150# FLANGE	HORSEPOWER	150*					X
B.(4) LWCO	1" NPT	DESIGN PRESSURE	15 P.S.I. STEAM					
C.(1) SAFETY VALVE	3" NPT	GROSS OUTPUT	5021 MBH.*					
D.( ) SAFETY VALVE		STEAM (FROM & AT 212°F)	5175 LBS./HR.*					
E.(1) BOILER BLOWDOWN	2" NPT	HEAT RELEASE: (FURNACE ONLY)	122,394 BTU/CJ.FT.*					
F.(1) SURFACE BLOWDOWN	1" NPT	RATED INPUT	6277 MBH.*					
G.(1) MANWAY	12" x 16"	HEATING SURFACE (ASME)	757 SQ.FT.					
H.(4) HANDHOLE	3" x 4"	FURNACE HEATING SURFACE	83.76 SQ.FT.					
J.(1) CLEANOUT PORT	17" ID	FURNACE VOLUME:						
K.(2) FEEDWATER	1 1/4" NPT	FURNACE ONLY	51.28 CU.FT.					
L.(1) AUXILIARY/VENT	2" NPT	STEAMING VOLUME	26.08 CU.FT.					
M.(1) LOW FIRE HOLD	1/2" NPT	STEAM RELEASE AREA	44.52 SQ.FT.					
N.(1) STACK TEMP	1/2" NPT	WATER CAPACITY:						
P.(1) SIGHT PORT	1 1/4" PIPE	(FULL)	1,349 GAL. @ 11216 LBS.					
Q.( )		(NWL)	1,153 GAL. @ 9,594 LBS.					
R.( )		SHIPPING WEIGHT:	13800 LBS.					
S.( )								

  

NOTES			
1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.			
2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.			
3. REAR DOOR SWING: (1) MIN SIDE, MAX REAR (2) MAX SIDE, MIN REAR			
4. BOILER DESIGN CODE ASME SECTION IV			
5. BOILER INSULATED WITH 2" OF INSULATION WITH 22 GAUGE STEEL JACKET.			
6. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.			
*7. HORSEPOWER AND RELATED INFO BASED ON 5 SqFt FIRING			

  

	CHECKED BY	?	DATE	
	DRAWN BY	?	DATE	
MOHAWK		BOILER MODEL		
		4-5-751-S15		
SCALE	DRAWING No			
1/48	?			

  

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.	
---	--